

Speed-Ease Ferrules

Hoff-Trex® Speed-Ease Ferrules

TPC Wire & Cable's Hoff-Trex® High Quality Speed-Ease™ tin plated ferrules are available in non-insulated or insulated styles for use in terminal blocks to avoid direct contact with wire and avoid the possibility of wire strand breakage. With size options ranging from small 26 AWG all the way up to 4/0, these ferrules are perfect for all size requirements.



Ratings



600V for Single Insulated

Max Operating Temp: 176°C

Engineered to Resist



Abrasion



Chemicals

Features & Benefits

Non-Insulated, Single Insulated and Twin Insulated Options

Suit the demands of various operations.

Available in Wire Sizes 26 AWG - 4/0

Perfect for small and large gauge requirements.

Color-Coded by AWG Size

Ease of identification.

Ordering Information

For complete product ordering information, please scan the QR Code or contact your TPC sales representative

Single Insulated Ferrules

Non-Insulated Ferrules

Part No.	Wire Size (AWG)	Color	Part No.	Wire Size (AWG)
FEB268	26 AWG	LIGHT BLUE	FE226	22 AWG
FEV268	26 AWG	VIOLET	FE206	20 AWG
FEB248	24 AWG	TURQUOISE	FE186	18 AWG
FEP248	24 AWG	PINK	FE167	16 AWG
FEQ228	22 AWG	ORANGE	FE147	14 AWG
FEW228	22 AWG	WHITE	FE1212	12 AWG
FEB208	20 AWG	BLUE	FE1010	10 AWG
FEW208	20 AWG	WHITE	FE815	8 AWG
FEG208	20 AWG	GRAY	FE615	6 AWG
FER188	18 AWG	RED	FE418	4 AWG
FEY188	18 AWG	YELLOW	FE1/022	1/0 AWG
FEBK168	16 AWG	BLACK	FE2/025	2/0 AWG
FER168	16 AWG	RED	FE3/025	3/0 AWG
FEG148	14 AWG	GRAY		
FEB148	14 AWG	BLUE		
FEO1212	12 AWG	ORANGE		
FEG1212	12 AWG	GRAY		
FEGN1012	10 AWG	OLIVE		
FEBK1012	10 AWG	BLACK		
FEY1012	10 AWG	YELLOW		
FEBR812	8 AWG	BROWN		
FEI812	8 AWG	IVORY		
FER812	8 AWG	RED		
FEI612	6 AWG	IVORY		
FEGN612	6 AWG	GREEN		
FEB612	6 AWG	BLUE		
FEBK416	4 AWG	BLACK		
FEY416	4 AWG	YELLOW		
FER216	2 AWG	RED		
FEB1/020	1/0 AWG	BLUE		
FEGN1/020	1/0 AWG	OLIVE		
FEY2/020	2/0 AWG	YELLOW		